



# XSLATE B10

## RUGGED TABLET PC

### PRODUCT SPECIFICATIONS

- MIL-STD 810G
- IP65
- CID2 ATEX Certified

#### FULLY RUGGED

- Magnesium Alloy Midframe
- MIL-STD-810G and IP65 Tested
- Elastomer Bumpers (Protected Glass/Touch Screen)
- Multiple 5' Drops

#### PROCESSOR

- Intel® Core™ i5-5350U Processor 1.8 GHz (2.9 GHz Turbo) with vPro™ Technology
- Intel® Core™ i7 vPro™ (Special Order Option)

#### OPERATING SYSTEMS

- Windows 8.1® Professional, 64-Bit
- Windows® 7 Professional, 64-Bit

#### DISPLAY

- 10.1" WXGA (1366 x 768) Rugged IPS LED Backlit Display
- 500 NITs Direct Bonded Screen
- 178° Viewing Cone (89° Off-Axis)
- Contrast Ratio: 800:1; Aspect Ratio: 16:9
- Ambient Light Sensor (ALS)
- 10-Finger Capacitive Touch Input with Glove and Wet Modes
- Pen Input based on Wacom Technology

#### GRAPHICS

- Intel® Integrated HD 6000 Graphics

#### MEMORY

- 8 GB DDR3L 1600

#### STORAGE OPTIONS

- Standard 128 GB SSD
- Up to 256 GB SSD

#### BATTERY LIFE

- Up to 8 Hour Battery Life (5300 mAh, 39.2 Whr, Single Battery)
- Up to 20 Hour Battery Life (8000 mAh, 59.2 Whr, Dual Battery)
- Hot Swappable External Battery

#### INTEGRATED COMMUNICATIONS

- Wireless LAN: 802.11ac
- Broadband: 4G LTE (Optional)
- GPS: Integrated, 2.0m Accurate Satellite
- Bluetooth® 4.0
- LAN: 10/100/1000 Gigabit Ethernet (RJ-45)

#### SECURITY

- Integrated Trusted Platform Module - TPM 2.0
- Kensington® Cable Lock Slot (Optional when using Top Handle)
- CAC Reader Module (Optional)

#### COLLABORATION

- Integrated Speaker and Dual Microphones
- Integrated Rear 8 Megapixel Camera with Flash
- Integrated Front 1080P FHD Webcam
- Integrated Fingerprint Scanner
- NFC (Optional)
- 1D/2D Barcode Scanner (Optional)

#### PORTS

- DC Power
- 2 x USB 3.0 Ports
- Micro SDXC
- Micro HDMI-out
- Micro SIM Card Reader
- RS232 True Serial Ready Port
- Stereo Headphones/Mic Mini-Jack, Smart Phone Headphone Compatible
- HDMI Input (Optional)

#### DIMENSIONS/WEIGHT

- 11.05" (28.1 cm) x 7.07" (18.0 cm) x 0.86" (2.2 cm) (W x H x D)
- Starting at 2.4 lbs (1.09 kg)

#### STATUS INDICATORS

- Power/Battery Status, Camera Active, HDD Activity

#### POWER SUPPLY

- Input Voltage: 19V with AC Adapter
- Supports 12-20V Input DC on Tablet

## SOFTWARE

- xCapture Pro
- Panel Control Center
- Bios Setup Utility
- Touch Mode Switcher\* (Wet and Glove touch modes)
- Sierra Wireless Skylight
- Validity Finger Print Manager App
- Ublox u-Center
- Wacom Pen App
- Screen rotate
- PC info

## ENVIRONMENTAL

- Tested to MIL-STD-810G Standards
- **Operating Temperature:** -34 °C to 60 °C / -30 °F to 140 °F
- **Cold Start:** -20 °C / -4 °F
- **Storage Temperature:** -30 °C to 70 °C / -22 °F to 158 °F
- **Transit Drop - Operating:** 5' (1.52 M) Drop Direct to Plywood over Concrete while System is Operating, 26 Drops
- **Vibration:** Minimum Integrity, Vehicle Vibration, US Highway Truck Vibration, Composite Wheel
- **Shock:** 40G Test Non-Operating
- **Humidity:** 23 °C to 60 °C / 73 °F to 140 °F, 95% Non-Condensing, 10 Days
- **Natural Cycle Humidity:** Fig 507.5-6, Non Hazardous B3 Class, 30 Days
- **Water Proofness:** Fig 506.5, 140L/hr, per sq/m, 15 Minutes
- **Wind Driven Rain:** Fig 506.5, 40 MPH Wind, 30 Minutes Per Side
- **Blowing Sand:** 20M/S, rate 1.1g/m<sup>3</sup> (+/- .3g) at high temperature of 60 °C
- **Blowing Dust:** velocity 8.9M/s dust concentration 3.9 g/m<sup>3</sup> at high temperature of 60 °C
- **Vibration:** Minimum Integrity, Vehicle Vibration, US Highway Truck Vibration
- **Temperature Shock:** -30°C to +70C within 5 minutes
- **Explosive Atmosphere:** Method 511.5, @60 °C, 20,000ft, 10,000ft, and 5,000ft
- **Contamination by Fluids:** 50/50 solution of water and bleach, 50/50 solution of water and hydrogen peroxide, diesel fuel, mineral based oil, Lysol disinfectant, denatured alcohol, Isopropyl alcohol
- **Altitude:** 40,000 Ft (12,192 M) Operating, 50,000 ft (15,240m) Non Operating

## IEC INGRESS TESTING

- IEC (60529) Ingress Tested to an IP65 Standard

## EMISSIONS & IMMUNITY

- **Tested to:** MIL-STD-461F
- **Immunity:** CISPR 24, EN55024 (US, CAN, EU)
- **Emissions:** EN55022, CISPR 22, CFR47 Part 15, Subpart B, ICES-003 for Class B (US, CAN, EU), CEC, Regulatory Bulletin No. 110915.02B (BCS), ERP Directive
- **Safety:** CB Scheme, IEC 60950 (US, CAN, EU), ANSI/ISA 12.12.01 Class I Div 2, A, B, C, D (US, CAN), ATEX

## ENVIRONMENT

- ROHS, Recycling Program: [www.xploretch.com/Environment/Recycle](http://www.xploretch.com/Environment/Recycle)
- Energy Star 6.1

## WARRANTY

- Standard 3 Year Limited Warranty
- Extended Warranty & xDefend Programs available. Please [contact Sales](mailto:contact@xploretch.com) or visit <http://www.xploretch.com/warranty> for further information.

## PERIPHERALS AND DOCKING

- xDock G2 IP55 Water and Dust-Resistant Vehicle Dock (12V compatible)
- G2 Office Productivity Dock
- 2-bay and 6-bay Battery Charging Stands

## ACCESSORIES

- Handle/Shoulder Strap with Pen and Tether
- Handstrap
- True Serial Cable
- Armortech Screen Protector
- External Battery Brackets, External Battery
- 12-16V Input, 19V Output DC-DC Converter (Cigarette Lighter Adapter)
- 12-32V Input, 19V Output DC-DC Converter (Heavy Duty Cigarette Lighter Adapter)
- 18 - 60V Input, 13.8 V Output DC - DC Converter, Direct Wire



\* Available Q4 2015

The Intel® Core™ vPro™ processor is designed to strengthen security across the enterprise.

© 2015 Xplore Technologies. All rights reserved. All product information is subject to change without notice. Xplore Technologies and Xplore are registered trademarks of Xplore Technologies in the United States and/or other countries. Microsoft Windows and Windows 7 and Windows 8 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel, the Intel logo, Atom, Intel Core and Core Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Bluetooth is a registered trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Xplore Technologies. All other trademarks and registered trademarks are the property of their respective owners.